

3要素 平均

酸素 80cc

蒸発倍数 負荷率

13.3	25.7%
11.7	26.3%
12.3	26.6%
13.0	26.9%
14.8	26.9%
13.1	27.2%
12.0	27.8%
14.3	28.4%
15.6	29.1%
14.4	29.2%
13.1	29.8%
14.0	30.2%
14.8	30.5%
13.2	31.4%
14.1	31.5%
14.6	31.6%
13.9	32.0%
15.6	33.7%
14.0	33.7%
14.0	33.7%
15.0	34.1%
12.8	34.4%
13.9	35.9%
14.5	36.1%
13.3	36.2%
14.0	37.3%
13.0	38.8%
15.1	39.1%
13.2	39.3%
13.9	41.6%
15.0	43.6%
13.4	44.2%
13.6	45.0%
15.3	45.1%
14.8	45.8%
14.3	47.8%

ホテル 天坊様

従来 ノーマル

蒸発倍数 負荷率

10.8	20.7%
10.7	20.9%
10.1	21.9%
12.5	22.0%
10.9	22.7%
10.6	23.0%
11.1	23.3%
11.2	23.4%
10.6	23.7%
10.5	24.3%
10.3	24.4%
10.9	24.6%
11.3	25.0%
11.0	25.4%
10.4	25.8%
11.5	27.4%
11.8	28.6%
11.6	28.8%
12.3	29.1%
11.7	29.2%
12.0	30.0%
11.9	30.2%
11.9	30.2%
12.1	30.2%
12.2	31.2%
12.2	33.1%

